

FlawGlo®

Product Data Sheet

SC 190

Solvent Cleaner/Remover

SC 190 is a solvent cleaner/remover for pre-cleaning, post-cleaning and removing excess surface penetrant from an inspection area before applying developer during liquid penetrant testing. SC 190 dries quickly without leaving any residue.

Appearance:

- Clear & volatile liquid

Properties:

- Density (20°C): 0.8 g/ml
- Flash Point: NA
- Processing Temperature: -10° to 52°C
- Compatible with any metals & many synthetic materials (compatibility for synthetic and ceramic materials must be check before use)

Compliance & Specifications:

- ISO 3452-2
- ASTM E165
- ASME B&PV

Application:

- Shake the can well before use and occasionally during use.
- Remove rust, oil, grease, and surface residues from the part using SC 190.
- Spray SC 190 from a distance of 7 to 12 inches (18 to 30 cm) at an approximate 45° angle to the test surface.
- Allow it to dry completely for a few minutes before applying SWP 139.

Shelf Life:

Recommended to use within 24 months, the product can be used for next 3 years, if it satisfies spraying & performance parameters.

Pack Sizes: Aerosol Can (1box of 10 cans), each can with Net Qty 400 ml

Disclaimer: Our technical advice, information and statements given verbally, in writing or in the form of test results, are offered for your guidance without warranty. No warranty of fitness for a particular purpose is made. It is the user's responsibility to test the suitability of each product for his intended process and applications. Our guarantee is limited to the consistent quality of our products.