

FlawGlo®

Product Data Sheet

SWP 139

Solvent Removable Red Dye Penetrant

SWP 139 is a Solvent Removable Red Dye Penetrant. It is a stable solution of petroleum distillates of high flash point, non-ionic surfactants and red dye. Due to this, it exhibits outstanding penetrating characteristics which provide for maximum reliability in locating surface-open flaws and discontinuities. SWP 139 can be used where a visible penetrant inspection system is required to detect surface breaking flaw.

Appearance:

- Red Mobile Liquid

Properties:

- Density (20°C): 0.87 g/ml
- Flash Point: Above 93°C
- Viscosity: 5 to 10 CST
- Processing Temperature: -10° to 52°C
- Suitable for detecting leaks in castings
- Compatible with any metal & many synthetic materials (compatibility with synthetic & ceramic materials must be checked before use)

Compliance & Specifications:

- ISO 3452-2
- ASTM E165
- ASME B&PV

Application:

- Apply SWP 139 by brushing, spraying or immersion on the test surface.
- Leave the penetrant dye to dwell for at least 10 minutes. Remove the excess penetrant from the surface, using a lint free cloth and SC 190 cleaner. Make sure not to use the cleaner directly on the test job.
- Continue with SD 175 developer to detect the flaws.

Shelf Life:

Recommended to use within 24 months, the product can be used for next 3 years if it satisfies spraying & performance parameters.

Pack Sizes: Aerosol Can (1 box of 10 cans), each can with Net Qty 400 ml
Barrel of 1 liter, 5 liter or 20 liter capacity

Disclaimer: Our technical advice, information and statements given verbally, in writing or in the form of test results, are offered for your guidance without warranty. No warranty of fitness for a particular purpose is made. It is the user's responsibility to test the suitability of each product for his intended process and applications. Our guarantee is limited to the consistent quality of our products.